

STRAINER

# Y Type Strainer

REF **EFC-119** ISSUED **05 Jun 2026**

## SPECIFICATIONS

Size	<b>DN15–DN600</b>
Pressure	<b>PN10–PN40</b>
End connection	<b>flanged (EN 1092-2/B)</b>
Face-to-face	<b>EN 558 Serie 1, DIN 3202 F1</b>

## STANDARDS

Design	<b>TS 11494</b>
Test	<b>EN 12266</b>



## MATERIALS

body	<b>grey cast iron, ductile iron, cast steel</b>	gasket	<b>compressed fibre</b>
bonnet	<b>grey cast iron, ductile iron, cast steel</b>		

STRAINER

# Y Type Strainer

SECTION Dimensions per size REF EFC-119

SIZE	L	H_MIN	H_MAX	D_PN10	K_PN10	D_PN16	K_PN16	D_PN25	K_PN25	D_PN40	K_PN40	WEIGHT
DN15	130	60	100	95	65	95	65	95	65	95	65	1.97 kg
DN20	150	70	120	105	75	105	75	105	75	105	75	2.98 kg
DN25	160	80	140	115	85	115	85	115	85	115	85	3.7 kg
DN32	180	85	150	140	100	140	100	140	100	140	100	5.6 kg
DN40	200	120	190	150	110	150	110	150	110	150	110	7.6 kg
DN50	230	135	220	165	125	165	125	165	125	165	125	9.8 kg
DN65	290	185	310	185	145	185	145	185	145	185	145	15.7 kg
DN80	310	205	340	200	160	200	160	200	160	200	160	24.9 kg
DN100	350	245	410	220	180	220	180	220	235	220	235	34 kg
DN125	400	290	470	250	210	250	210	270	220	270	220	43 kg
DN150	480	330	530	285	240	285	240	300	250	300	250	54 kg
DN200	600	390	620	340	295	340	295	360	310	375	320	118 kg
DN250	730	530	850	395	350	405	355	425	370	450	385	177 kg
DN300	850	560	1050	445	400	460	410	485	430	515	450	275 kg
DN350	980	620	1100	505	460	520	470	555	490	580	510	310 kg

## Y Type Strainer

Dimensions per size (continued) · EFC-119

SIZE	L	H_MIN	H_MAX	D_PN10	K_PN10	D_PN16	K_PN16	D_PN25	K_PN25	D_PN40	K_PN40	WEIGHT
<b>DN400</b>	1100	710	1210	565	515	580	525	620	550	660	585	418 kg
<b>DN450</b>	1200	800	1400	615	565	640	585	670	600	685	610	495 kg
<b>DN500</b>	1250	985	1700	670	620	715	650	730	660	755	670	1100 kg
<b>DN600</b>	1450	1100	1900	780	725	840	770	845	770	890	795	1300 kg

*All dimensions in millimetres unless stated otherwise. Values are nominal; tolerances confirmed at quote.*