

FIRE HYDRANT

Fire Valve Straight Type

MODEL VDYB-16 REF EFC-161 ISSUED 05 Jun 2026

SPECIFICATIONS

Size	DN40–DN65
Pressure	PN16
End connection	flanged (EN 1092-3/B)
Face-to-face	VisVana Design
Media	water, fire-fighting water

ACTUATION

- manual handwheel — GG25 or Bronze Rg5 handwheel

STANDARDS

Design	BS 5041, DIN 86211
Test	EN 12266

APPLICATIONS

- fire fighting
- fire hydrant systems



MATERIALS

body	bronze, carbon steel	disc	bronze, carbon steel
seat	elastomer	stem	brass, stainless steel
gasket	elastomer, compressed fibre	bonnet	bronze, carbon steel
packing	graphite, PTFE	handwheel	grey cast iron, bronze

FEATURES

- Screwed bonnet construction
- Straight-type body configuration
- Coupling options: Storz, BS 336, Nor, Nakajima
- Flange options available in ASME, JIS, VG in addition to EN 1092-3/B
- Fixed and blind coupling accessories included
- Chain/rope retainer for coupling cap

FIRE HYDRANT

Fire Valve Straight Type

SECTION Dimensions per size REF EFC-161

SIZE	L	L1	H_CLOSE	H_OPEN	G	D1	C	OD	OK	OG	B	F	N_OD	WEIGHT
DN40	150	220	160	170	1-1/2" inch	98	140	150	110	84	14	2	4-18	6.5 kg
DN50	165	235	165	180	2" inch	98	140	165	125	99	16	2	4-18	8 kg
DN65	200	265	185	205	2-1/2" inch	126	150	185	145	118	16	2	4-18	11.5 kg

All dimensions in millimetres unless stated otherwise. Values are nominal; tolerances confirmed at quote.