

BUTTERFLY VALVE

Extension Shaft Wafer Butterfly Valve

REF **EFC-277** ISSUED 05 Jun 2026

SPECIFICATIONS

Size	DN50–DN1000
Pressure	PN10–PN16
End connection	wafer (DIN 2501) / wafer (ANSI) / wafer (BS 4504) / wafer (JIS)
Face-to-face	API 609, DIN 3202, ISO 5752, BS 5155
Temperature	-30°C to 135°C
Media	chemicals, air, water, steam, oil, acids, salts

STANDARDS

Design	API 609, ANSI 16.34, JIS B2064, GB/T 12238
Test	API 598

APPROVALS & CERTIFICATIONS

- WRAS (available)
- NSF/ANSI 61 (available)
- DVGW (available)
- LR (Lloyd's Register)
- ECM (Ente Certificazione Macchine)
- ISO
- EAC
- CE
- Bureau Veritas
- ACS (Attestation de Conformite Sanitaire)
- WRAS Approved Product

APPLICATIONS

- Buried pipeline systems
- Insulated piping
- Hard-to-access installations



SIZE in DN	C	d0	K	E	z-d	g	h	p	bXI	PN16		PN10		ANSI 150		JIS 10K		
										D1	n-Ød1	D1	n-Ød1	D1	n-Ød1	D1	n-Ød1	
2	50	42	12.6	77	50	4-7	35	3	9	3X16	125	4-18	125	4-18	120.5	4-19	120	4-19
2.5	65	44.7	12.6	77	50	4-7	35	3	9	3X16	145	4-18	145	4-18	139.5	4-19	140	4-19
3	80	45.2	12.6	77	50	4-7	35	3	9	3X16	160	8-18	160	8-18	152.5	4-19	150	4-19
4	100	52.1	15.77	90	70	4-9	55	3	11	5X19	180	8-18	180	8-18	190.5	8-19	175	8-19
5	125	54.4	18.92	90	70	4-9	55	3	14	5X19	210	8-18	210	8-18	216	8-22	210	8-23
6	150	55.8	18.92	90	70	4-9	55	3	14	5X19	240	8-23	240	8-23	241.5	8-22	240	8-23
8	200	60.6	22.1	125	102	4-12	70	3.5	17	5X19	295	12-23	295	8-23	298.5	8-22	290	12-23
10	250	65.6	28.45	125	102	4-12	70	3.5	22	8X28	355	12-27	350	12-23	362	12-25	355	12-25
12	300	76.9	31.6	125	102	4-12	70	3.5	22	8X28	410	12-27	400	12-23	432	12-25	400	16-25
14	350	76.9	31.6	125	102	4-12	70	3.5	22	8X28	470	16-27	460	16-23	476	16-29	445	16-25
16	400	86.5	33.15	175	140	4-18	100	4	24	10X50	525	18-30	515	16-27	540	16-29	510	16-27
18	450	105.6	38	175	140	4-18	100	4	27	10X50	585	20-30	565	20-27	578	16-32	565	20-27
20	500	127	41.15	175	140	4-18	100	4	32	10X50	650	20-33	620	20-27	635	20-32	620	20-27
24	600	152	50.65	210	165	4-23	130	5	36	2-18X60	770	24-36	725	20-30	749.5	20-35	730	24-33
28	700	163	55	300	254	8-18	200	5.5		2-18X63	840	24-36	840	24-30	863.5	28-35	840	24-33
30	750	165	55	300	254	8-18	200	5.5		2-18X63	914	24-39	914	24-33	914.5	28-11/4	900	24-33
32	800	188	55	300	254	8-18	200	5.5		2-18X63	950	24-39	950	24-33	978	28-41	950	28-33
36	900	203	75	300	254	8-18	200	5.5		2-20X100	1050	28-39	1050	28-33	1086	32-41	1050	28-33
40	1000	216	85	300	254	8-18	200	5.5		2-20X100	1170	28-42	1160	28-36	1200	36-41	1160	28-39
42	1050	251	95	300	254	8-18	200	5.5		2-25X140	1257	32-44	1257	32-37	1257.5	36-41	1270	28-39
48	1200	276	105	350	298	8-23	230	5.5		2-28X140	1390	32-50	1380	32-41	1422.5	40-41	1380	32-39

MATERIALS

body	Cast Iron, Ductile Iron, Carbon Steel, Stainless Steel	disc	Ductile Iron, Carbon Steel, Stainless Steel, Stainless Steel / PTFE, Copper Alloy
stem	Stainless Steel	seat	Elastomer, Fluoropolymer
o ring	Elastomer	bushing	Fluoropolymer, Copper Alloy

FEATURES

- Extension shaft allows valve operation without excavation of buried pipelines
- Thermal break option to prevent heat transfer in insulated systems
- Compact wafer-style body
- Custom shaft lengths, materials, and accessories available on request
- Wafer-style butterfly valve with lever handle
- Rubber-lined body bore (seat integral with body)
- Disc visible in closed position
- Stem with packing gland arrangement
- Flanged drilling patterns available for PN10, PN16, ANSI 150 and JIS 10K

OPTIONS & NOTES

- Global Certifications – WRAS, NSF/ANSI 61, DVGW available
- Custom Configurations – Special shaft lengths, materials, and accessories
- Our products hold up to 10 international authoritative certification certificates

BUTTERFLY VALVE

Extension Shaft Wafer Butterfly Valve

SECTION Technical drawing REF EFC-277

